

3

2003 P 03030

32

(19)



Europhes Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 170 932 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
09.01.2002 Bulletin 2002/02

(51) Int Cl.7: H04M 1/57, H04M 1/27

(21) Application number: 00401956.8

(22) Date of filing: 06.07.2000

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• Maquaire, Fanny
06000 Nice (FR)
• Lefaucheur, Laurent
06700 St Laurent du Var (FR)

(71) Applicants:
• TEXAS INSTRUMENTS FRANCE
06271 Villeneuve Loubet Cédex (FR)
Designated Contracting States:
FR
• Texas Instruments Incorporated
Dallas, TX 75251 (US)
Designated Contracting States:
BE CH DE DK ES FI GB GR IE IT LI LU MC NL PT
SE AT CY

(74) Representative: Jacobson, Claude et al
Cabinet Lavoix 2, Place d'Estienne d'Orves
75441 Paris Cedex 09 (FR)

(54) Audible identification of caller and callee for mobile communication device

(57) A mobile communications device (10) stores a database of telephone numbers (40), with one or more of the telephone numbers associated with respective audio files in an audio file database (44) and voice templates in a voice template database (42). Processing circuitry (30) implements voice activated dialing where one of the telephone numbers in the telephone number database (40) is dialed in response to identifying a match

between an audio input from a user and one of templates in the voice template database (42). An audio file from the audio file database is played in response to a match. The processing circuitry (30) further detects originating telephone number associated with incoming telephone calls and, if the originating telephone number is associated with an audio file, plays the associated audio file from the same audio file database used for the voice activated dialing.




FIG. 3

EP 1 170 932 A1




FIG. 4

Description

BACKGROUND OF THE INVENTION

1. TECHNICAL FIELD

[0001] This invention relates in general to telecommunications and, more particularly, to caller identification for mobile communications devices.

2. DESCRIPTION OF THE RELATED ART

[0002] For many years, the communications industry has improved the functionality of the telephone system. New services, such as Caller ID, Call Waiting, and Voice Activated Dialing are examples of functions that have been added to the phone system to improve the quality of communications. In addition to new functionality, mobile communication devices have evolved to provide communication resources apart from a wireline connection.

[0003] Because of the cost of wireless communications, many users desire to screen calls, i.e., they only answer calls from certain people. Most mobile communications systems provide Caller ID functions to mobile phones to aid with screening. With Caller ID, the name of the calling party is presented on the phone's display. This requires the user to look at the phone's display to identify the caller. This can be very inconvenient if the phone is not located in the immediate vicinity of the called party. If the called party is operating a vehicle when the call arrives, viewing the phone's display can be dangerous.

[0004] To reduce this risk, some mobile phones provide a distinctive ring that can be associated with groups of telephone numbers. For example, a first ring type could be associated with number of co-workers, a second ring type could be associated with family members, and a third ring type could be associated with clients. However, it is not practical to provide different ring types for each caller, because it would be impossible to remember the associations for more than a few people.

[0005] Accordingly, a need exists for a more efficient method and apparatus for identifying callers using a mobile communications device.

BRIEF SUMMARY OF THE INVENTION

[0006] The present invention provides a mobile communications device comprising a database of telephone numbers, with one or more of the telephone numbers associated with respective audio files and voice templates. Voice activated dialing circuitry dials one of the telephone numbers in response to identifying a match between an audio input from a user and one of templates, and plays the associated audio file in response to the match. Caller identification circuitry detects an originating telephone number associated with an incom-

ing telephone call and, if the originating telephone number is associated with an audio file, playing the associated audio file.

[0007] The present invention provides significant advantages over the prior art. First, it allows for an audible indication of the calling party for the most frequently used numbers. Second, the capability for audible indication, in the user's own voice, can be accomplished without additional memory, since the audio files are shared with the voice activated dialing function. Accordingly, the additional power and cost associated with the audible caller identification function is minimal.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0008] For a more complete understanding of the present invention, and the advantages thereof, reference is now made to the following descriptions taken in conjunction with the accompanying drawings, in which:

Figure 1 illustrates a perspective view of a mobile communications device;

Figure 2 illustrate a block diagram of the mobile communications device of Figure 1 with audible caller identification circuitry;

Figure 3 illustrates a functional block diagram of the operation of Figure 2 with respect to audible caller identification and voice activated dialing; and

Figure 4 illustrates a flow diagram illustrating the operation of an audible caller identification task.

DETAILED DESCRIPTION OF THE INVENTION

[0009] The present invention is best understood in relation to Figures 1 - 4 of the drawings, like numerals being used for like elements of the various drawings.

[0010] Figure 1 illustrates a mobile communication device for providing wireless communications. The mobile communication device 10 of Figure 1 could be, for example, a cellular phone, smart phone, satellite phone, portable computer or a PDA (personal digital assistant) with wireless communications capabilities. The overall look of the device 10 could vary according to its capabilities; however, most mobile communication devices will have similar attributes: a display 12, an input keypad 14 (which may be integrated with the display 12 using a touch screen), a microphone 16, a conversation speaker 18 (for audio when pressed to the user's ear), a loudspeaker/ringer 20, and an antenna 22.

[0011] In operation, the mobile communications device 10 has both voice activated dialing capabilities and audible caller identification capabilities. For the voice activated dialing, the internal circuitry of the mobile communications device 10 stores information used for voice

activated dialing in a memory subsystem (see Figure 2). The information stored by the mobile communications device 10 includes a telephone number database (storing a plurality of frequently called numbers), a voice template database (storing voice templates used to recognize an utterance by the user indicative of a particular telephone number), and an audio file database (for confirmation of a voice dialed number), typically in the users own voice).

[0012] When a user creates a new entry for the voice activated dialing system, he or she speaks the designation for the new number (such as "John", "work", or "home") and enters the number, either by speaker independent voice recognition, or by using the telephone keypad. The spoken designation is stored as an audio file (such as a *.wav file) and a template is made from the audio file; this template is used later for speech recognition. For each voice activated dialing entry, the telephone number, template and audio file are linked.

[0013] The user may call any entry on the voice dialing list by speaking "Call" (or another suitable command) and the designation. Accordingly, "call home" would result in the telephone number associated with "home" being dialed. To identify the desired telephone number, the voice dialing circuitry parses the utterance (i.e., separates "call" and "home") and compares the stored templates with the designation portion of the utterance (i.e., "home"). Using techniques well known in the art, the designation portion of the utterance is matched to one of the templates, typically by assigning a score to each comparison. If the comparison with the best score meets a certain threshold, a match occurs, and the phone number and audio file associated with the matching template are retrieved. Prior to dialing, however, the audio file associated with the matching template is played to the user as a confirmation. Thus, if the user voice dials using "call John" and the mobile communications device 10 responds with "calling Jean" (where "Jean" is the audio file associated with the errantly matched template), the user can cancel the phone call before the connection is made. The voice dialing database could be used for other commands as well, such as "page John", depending upon the capabilities of the mobile communications device 10.

[0014] The present invention uses the same audio files created for voice activated dialing for caller identification. On an incoming call, the mobile communications device 10 receives data indicating the originating telephone number. This information is compared to the telephone numbers stored in the voice activated dialing database. If there is a match, the audio file associated with that number is retrieved and played. Accordingly, the user receives an audible indication of the calling party prior to answering the phone.

[0015] Figure 2 illustrates a basic block diagram showing the circuitry used in the voice activated dialing and the audible caller identification functions. Processing circuitry (typically, a digital signal processor, gener-

ally referred to as a "DSP" or a multiple microprocessor/DSP system) 30 is coupled to a transceiver 32, memory subsystem 38, keypad 14, microphone 16, and audio output circuitry 36. Output circuitry 36 is coupled to speaker 20. Antenna 22 is coupled to transceiver 32. Memory subsystem 38 includes locations for telephone numbers 40, templates 42, audio files 44 and programs 46. It should be noted that other data would also be stored in memory subsystem 38.

[0016] Memory subsystem 38 may include memory internal to processing circuitry 30, external to processing circuitry 30, or a combination of internal and external memory. Processing circuitry 30 may receive data and commands through keypad 14, microphone 16 (using speaker dependent and/or speaker independent voice recognition), and from telecommunications signals via transceiver 32.

[0017] During operation of the mobile communications device 10, the processing circuitry will execute a number of tasks. For example, the processing circuitry will be monitoring inputs from the keypad 14, microphone 16 and transceiver 32. If, for example, a number is dialed using the keypad, the processing circuitry will accumulate numbers from the keypad 14, and initiate a connection via one or more base stations. Similarly, a voice input via the microphone would be monitored via a speech recognition task to determine whether a command, such as "call", was being issued. If so, the designated party would be determined using speech recognition, and the telephone number would be retrieved from memory subsystem 38 using a voice activated dialing task.

[0018] Processing circuitry 30 also monitors transceiver 32 for incoming calls directed to the mobile communications device 10. When such a call is received, the originating number is received using typical caller identification techniques. The originating number is compared to numbers in the telephone number database 40. If there is a match, the associated audio file is played through speaker 20 and the information is presented on display 12.

[0019] Figure 3 illustrates a block diagram showing the interaction between the voice activated dialing task 50 and the audible caller identification task 52. Both the voice activated dialing task 50 and the caller identification task 52 access the audio files database 44 and the telephone numbers database 40.

[0020] Figure 4 illustrates a block diagram of the audible caller identification task 52. In block 60, the task 52 waits for an incoming call directed to the mobile communications device 10. When an incoming call is received, the originating number is derived from the data stream in block 62. The originating number is compared to numbers in the telephone number database 40 used for voice activated dialing. If there is a match in decision block 64, the audio file associated with the matching telephone number is accessed from the audio file database 44. This audio file is played to the user in block 68,

if the feature is enabled (in many circumstances, the user will not want the name to be audibly output, so the feature may be disabled by the user). In block 70, the name and number are visually displayed to the user.

[0021] In addition to playing the audio file from the audio file database, the processing circuitry 30 may also play an accompanying audio file, such as "you have a call from" or "is calling". Accordingly, the complete audio output from the caller identification task could be "you have a call from home" or "john is calling." The accompanying recording could be synthesized speech or recorded by the user.

[0022] If, in decision block 64, the originating number is not found in the telephone database 40, then the name and number is output on the display 12 without playing the audio file. Additionally, or in the alternative, a distinctive ring could be played, where the distinctive ring indicates a group of one or more telephone number associated with the calling party.

[0023] The present invention provides significant advantages over the prior art. First, it allows for an audible indication of the calling party for the most frequently used numbers. Second, the capability for audible indication, in the user's own voice, can be accomplished without additional memory, since the audio files are shared with the voice activated dialing function. Accordingly, the additional power and cost associated with the audible caller identification function is minimal.

[0024] Although the Detailed Description of the invention has been directed to certain exemplary embodiments, various modifications of these embodiments, as well as alternative embodiments, will be suggested to those skilled in the art. The invention encompasses any modifications or alternative embodiments that fall within the scope of the Claims.

Claims

1. A mobile communications device comprising:
 - a database of telephone numbers, one or more of the telephone numbers associated with respective audio files and voice templates; voice activated dialing circuitry for dialing one of the telephone numbers in response to identifying a match between an audio input from a user and one of templates, and for playing the associated audio file in response to said match; and;
 - caller identification circuitry for detecting an originating telephone number associated with an incoming telephone call and, if said originating telephone number is associated with an audio file, playing the associated audio file.
2. The mobile communications device of claim 1 and further comprising a display for displaying name associated with a telephone caller.
3. The mobile communications device of claim 2 wherein the display further displays said originating telephone number.
4. The mobile communications device of claim 1 wherein said caller identification circuitry further plays a distinctive ring associated with said originating telephone number if the originating telephone number is not associated with an audio file.
5. The mobile communications device of claim 1 wherein said audio files are recordings of the user's voice.
6. The mobile communications device of claim 1 wherein said mobile communications device is a cellular telephone.
7. The mobile communications device of claim 1 wherein said mobile communications device is a smart phone.
8. The mobile communications device of claim 1 wherein said mobile communications device is a personal digital assistant.
9. The mobile communications device of claim 1 wherein said mobile communications device is a portable computer.
10. A method of interfacing with a mobile communications device, comprising the steps of:
 - storing frequently called numbers in a telephone number database, one or more of the telephone numbers in said telephone number database associated with respective audio files and voice templates;
 - receiving an audio input from a user for dialing one of said frequently dialed telephone numbers;
 - in response to receiving said audio input, identifying a match between said audio input and one of templates and playing the associated audio file in response to said match; and;
 - detecting an originating telephone number associated with an incoming telephone call and, if said originating telephone number is associated with an audio file, playing the associated audio file.
11. The method of claim 10 and further comprising the step of displaying name associated with a telephone caller.
12. The method of claim 11 and further comprising the

step of displaying said originating telephone number.

13. The method of claim 10 and further comprising the
step of playing a distinctive ring associated with said
originating telephone number if the originating tele- 5
phone number is not associated with an audio file.
14. The method of claim 10 wherein said audio files are
recordings of the user's voice. 10
15. A mobile communications device comprising:
- a database of telephone numbers, one or more
of the telephone numbers associated with re- 15
spective audio files and voice templates;
processing circuitry for executing a first task for
performing voice activated dialing using said
telephone numbers, audio files and voice tem-
plates and for executing a second task for per- 20
forming caller identification playing one of said
audio files in response to receiving a call from
an originating telephone number associated
with said one audio file.

25

30



35

40

45

50

55






FIG. 3




FIG. 4



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 40 1956

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y	WO 99 45687 A (YABLON) 10 September 1999 (1999-09-10) * page 8, line 17 - line 22 * * page 9, line 17 - line 23 * * page 11, line 2 - line 24 * * page 12, line 3 - line 9 * * page 16, line 14 - line 19 * * page 19, line 20 - page 20, line 25 * * figures 1,12,13 *	1-3, 6-12,15	H04M1/57 H04M1/27
Y	GB 2 268 663 A (NIPPON ELECTRIC CO) 12 January 1994 (1994-01-12) * abstract * * page 4, line 18 - page 7, line 11 * * figures 2,3 *	1-3, 6-12,15	
A	DE 198 32 069 A (SIEMENS AG) 20 January 2000 (2000-01-20) * abstract * * column 1, line 49 - line 53 * * column 1, line 60 - column 2, line 2 * * column 2, line 26 - column 3, line 41 * * figure 2 *	1-3, 10-12,15	TECHNICAL FIELDS SEARCHED (Int.Cl.7) H04M
A	US 5 583 919 A (TALVARD ET AL) 10 December 1996 (1996-12-10) * abstract * * column 2, line 25 - column 3, line 9 * * column 8, line 66 - column 9, line 9 * * figures 3,4 *	1,5,6, 10,14,15	
-/--			
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 29 November 2000	Examiner Fragua, M
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons</p> <p>8 : member of the same patent family, corresponding document</p>			

EPO FORM 1503 (03.02) (P&C/01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 40 1956

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	US 5 550 900 A (ENSOR ET AL) 27 August 1996 (1996-08-27) * column 4, line 47 - line 64 * * column 6, line 8 - line 21 * * column 8, line 2 - line 26 * * column 9, line 52 - line 64 * * column 10, line 35 - line 51 * * figure 4 *	1-3, 10-12, 15	
A	US 5 826 199 A (MAEDA) 20 October 1998 (1998-10-20) * column 4, line 53 - column 5, line 12 * * column 8, line 39 - line 55 * * figures 4, 5 *	1, 10, 15	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 29 November 2000	Examiner Fragua, M
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (P04001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 40 1956

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

29-11-2000

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
WO 9945687	A	10-09-1999	US	5764731 A	09-06-1998
GB 2268663	A	12-01-1994	JP	6006428 A	14-01-1994
DE 19832069	A	20-01-2000	WO	0004695 A	27-01-2000
US 5583919	A	10-12-1996	FR	2711872 A	05-05-1995
			EP	0650283 A	26-04-1995
US 5550900	A	27-08-1996	BR	9506139 A	13-10-1999
			CA	2165713 A	30-06-1996
US 5826199	A	20-10-1998	JP	2606142 B	30-04-1997
			JP	8008812 A	12-01-1996
			GB	2290437 A, B	20-12-1995

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82